Commonwealth of the Philippines
Department of the Interior
QUEZON CITY
City Council

ORDINANCE Numbered 93

AN ORDINANCE APPROPRIATING THE AMOUNT OF ₱400.00 FROM THE UNAPPROPRIATED FUNDS OF QUEZON CITY TO DEFRAY THE COST AND INSTALLATION OF AN UNDERGROUND TANK FOR GASOLINE.

WHEREAS, the City Engineer, in his letter of October 4, 1940 to the City Council, manifested the desirability and advantages of having a gasoline pump for the exclusive use of Quezon City;

WHEREAS, he also stated that the Standard Vacuum Oil Company has consented to loan the City a gasoline pump free of charge on condition that the City provides an underground tank which is estimated to cost between ₱340.00 and ₱360.00 for its installation;

NOW, THEREFORE, be it ordained by the City Council of Quezon City, that:

Section 1. The sum of ₱400.00 is hereby appropriated from the unappropriated funds of Quezon City to defray the cost and installation of an underground tank for gasoline.

Section 2. The amount set aside in this Ordinance shall be expended solely for the specific purpose for which authorized.

Section 3. This Ordinance shall take effect upon its passage.

Unanimously passed, October 7, 1940.

(SGD.) TOMAS B. MORATO
City Mayor

1519

ATTEST:

[illegible]
City Secretary

Created with nitroPDF professional
download the free trial online at nitropdf.com/professional

[illegible]	10 cm.	No. 1. - Passing 4-inch and retained on 1-1/2" circular opening, uniformly grade.
[illegible]	7.5 cm.	No. 2. - Passing 2-1/2-inch and retained on 1" circular opening, uniformly graded.
[illegible]	7.5 cm.	No. 3.- Passing 1-1/2-inch and retained on 3/4-inch circular opening, uniformly graded.
[illegible]		No. 4. - Screenings passing 3/4-inch circular opening or other approved cementatious material.

The surfacing of a gravel road shall be composed of a [illegible] foundation and gravel bounded together with [illegible] and clay, or other approved cementatious material [illegible]. The surfacing shall be laid in three courses as follows:

Course	Depth Compacted	Name and Size of Gravel Aggregate
[illegible]	15 cm. to 20 cm.	No. 0 - Width, 3" to 6", Depth, 6" to 8", Length, 6" to 15"
[illegible]	7.5 cm.	No. 2 - Passing 2-1/2-inch and retained on 1-inch square opening, uniformly graded.
[illegible]	7.5 cm.	No. 3 - Passing 1-inch and retained on 1/2-inch square opening, uniformly graded.
[illegible]		No. 4 - Pea gravel, or coarse sand with clay, or other approved cementatious material.

[illegible]:- The donation of macadam or [illegible] shall not be considered unless it has been [illegible] a surface treatment of asphalt in accordance with the standard specifications of the Bureau of [illegible] for asphalt surface-treating of macadam [illegible].

[illegible]:- Plans, profiles, typical [illegible] of subdivision roads offered for donation [illegible] on said roads shall be submitted [illegible] by the City Engineer.

[illegible] issue or cause to be [illegible] a deed of [illegible] of title of the road to be donated.

Created with nitroPDF professional
download the free trial online at nitropdf.com/professional